

# DRYER-D

บริษัท เอ็มทีเอส ซีเอ็นซี ซิสเต็ม จำกัด 48/300 ซ.หทัยราษฎร์ 37 ถ.หทัยราษฎร์ แขวง สามวาตะวันตก เขตคลองสามวา กรุงเทพฯ 10510

โทร: 02-9067988 MB: 092-2753497 Line ID : dryer-d , Line@ : @dryer-d E-mail: dryer.dservice@gmail.com www.dryer-d.com

## Specification Explosion-Proof Dehumidifier Model: DDH-138BCF

	Model	DDH-138BCF
	Series	Explosion-Proof Dehumidifier
Sealed explosion-proof junction box	Explosion-Proof grade	Ex db ib mb IIB T4 Gb
	Voltage/Cycle	220V / 50Hz
Explosion-proof bolt	Power Input (W)	2000W
	Running Current	9.0A
Key-press type control panel	Dehumidifying Capacity	138L/Day (30°C, 80%RH)
	Humidity Set	30% - 90% RH
	Humidity level can be set	+/- 1%RH
	Working mode humidity set	Stop working when humidity is lower than the required 3%.
	Mode of Defrosting	Auto
	Coverage area	180 - 200 sq.m (High 3 m)
	Refrigerant	R410A / R22
	Air Flow	1200 m <sup>3</sup> /h, 706 cfm
	Fan Speed	Fan cannot be adjusted
	Drainage Method	Direct Drain External pipe 16 mm
	Working temperature range	5°C- 38°C
	Maneuverability	4 Casters, Handle
	Noise	≤60dB at a distance of 1 m.
	Compressor	Rotary
	Safety / Features	3 min delay protection Show Failure Code, Auto restart Timer 1-24 Hr, Show Room Temp & Coil Temp
	Color	White
	Unit Dimension (mm.)	480*406*924 (±5).
	N/W	52Kg (±2)