

# DRYER-D

บริษัท เอ็มทีเอส ซีเอ็นซี ซิสเต็ม จำกัด 48/300 ซ.หทัยราษฎร์ 37 ถ.หทัยราษฎร์ แขวง สามวาตะวันตก เขตคลองสามวา กรุงเทพฯ 10510

โทร: 02-9067988 MB: 092-2753497 Line ID : dryer-d , Line@ : @dryer-d E-mail: dryer.dservice@gmail.com www.dryer-d.com

## Specification Dehumidifier Model: DDH-192LT

|  |  |  |
|--|--|--|
|  | <b>Model</b>   | <b>DDH-192LT</b>   |
|  | <b>Series</b>  | Industrial Low Temperature   |
|  | <b>Voltage/Cycle</b>   | 380V / 50Hz  |
|  | <b>Power Input (W)</b>   | 3000W  |
|  | <b>Dehumidifying Capacity</b>  | 192 L/Day  |
|  | <b>Humidity Set</b>  | 30% - 95%RH<br>(0-5 ° C: 75%RH)<br>(5-8 ° C: 70%RH)<br>(8-16 ° C: 60%RH) |
|  | <b>Humidity level can be set</b>   | +/- 1%RH   |
|  | <b>Working mode humidity set</b>   | Stop working when humidity is lower than the required 3%.                |
|  | <b>Coverage area</b>   | 40 - 80 sq.m (High 3 m)  |
|  | <b>Refrigerant</b>   | R410A / R22  |
|  | <b>Air Flow</b>  | 2000 m <sup>3</sup> /h, 1177 cfm   |
|  | <b>Fan Speed</b>   | Fan cannot be adjusted   |
|  | <b>Drainage Method</b>   | Direct Drain External pipe 16 mm   |
|  | <b>Working temperature range</b>   | 0°C- 8°C (32°F – 46.4°F)   |
|  | <b>Maneuverability</b>   | 4 Casters  |
|  | <b>Noise</b>   | ≤60dB at a distance of 1 m.  |
| <b>Compressor</b>  | Rotary   |  |
| <b>Safety / Features</b>   | 3 min delay protection, Show Failure Code, Auto restart, Timer 1-24 Hr, Show Room Temp, Phase Fault, Phase Lose, Automatic Defrost, Overload Protection, Coil Temp |  |
| <b>Color</b>   | White  |  |
| <b>Unit Dimension (mm.)</b>  | 615*470*1595 (±5).   |  |
| <b>N/W</b>   | 98Kg (±2)  |  |

