

DRYER-D

บริษัท เอ็มทีเอส ซีเอ็นซี ซิสเต็ม จำกัด 48/300 ซ.หทัยราษฎร์ 37 ถ.หทัยราษฎร์ แขวง สามวาตะวันตก เขตคลองสามวา กรุงเทพฯ 10510

โทร: 02-9067988 MB: 092-2753497 Line ID : dryer-d , Line@ : @dryer-d E-mail: dryer.dservice@gmail.com www.dryer-d.com

Specification High Temperature Resistance Dehumidifier Model: DDH-288HT



Model	DDH-288HT
Series	Industrial High Temperature
Voltage/Cycle	380V / 50Hz
Power Input (W)	4400W
Dehumidifying Capacity	288 L/Day
Hourly dehumidifying	12kg/h
Humidity Set	30% - 95%RH
Humidity level can be set	± 1%RH
Humidity control accuracy	± 3%RH
Working mode humidity set	Stop working when humidity is lower than the required 3%.
Coverage area	350 - 450 sq.m (High 3 m)
Refrigerant	R22
Air Flow	2300 m ³ /h, 1353 cfm
Fan Speed	Fan cannot be adjusted
Drainage Method	Direct Drain External pipe 16 mm
Working temperature range	30°C- 55°C (86°F – 131°F)
Maneuverability	4 Casters
Noise	≤65dB at a distance of 1 m.
Compressor	Rotary
Safety / Features	3 min delay protection, Show Failure Code, Auto restart, Timer 1-24 Hr, Show Room Temp, Phase Fault, Phase Lose, Automatic Defrost, Overload Protection, Coil Temp
Color	White
Unit Dimension (mm.)	783*470*1603 (±5).
N/W	110Kg (±2)