

# DRYER-D

บริษัท เอ็มทีเอส ซีเอ็นซี ซิสเต็ม จำกัด 48/300 ซ.หทัยราษฎร์ 37 ถ.หทัยราษฎร์ แขวง สามวาตะวันตก เขตคลองสามวา กรุงเทพฯ 10510

โทร: 02-9067988 MB: 092-2753497 Line ID : dryer-d , Line@ : @dryer-d E-mail: dryer.dservice@gmail.com www.dryer-d.com

## Specification Explosion-Proof Dehumidifier Model: DDH-480BCF



Explosion-proof bolt



Key-press type control panel

Model	DDH-480BCF
Series	Explosion-Proof Dehumidifier
Explosion-Proof grade	Ex db ib mb IIB T4 Gb
Voltage/Cycle	380V / 50Hz
Power Input (W)	8000W
Dehumidifying Capacity	480L/Day (30°C, 80%RH)
Hourly Dehumidifying	20kg/h (30°C, 80%RH)
Humidity Set	30% - 90% RH
Humidity level can be set	+/- 1%RH
Working mode humidity set	Stop working when humidity is lower than the required 3%.
Mode of Defrosting	Auto
Coverage area	650 - 700 sq.m (High 3 m)
Refrigerant	R410A / R22
Air Flow	4000 m <sup>3</sup> /h, 2354 cfm
Fan Speed	Fan cannot be adjusted / 4 Fans
Drainage Method	Direct Drain External pipe 16 mm
Working temperature range	5°C- 38°C
Maneuverability	4 Casters
Noise	≤60dB at a distance of 1 m.
Compressor	Rotary
Safety / Features	3 min delay protection Show Failure Code, Auto restart Timer 1-24 Hr, Show Room Temp & Coil Temp
Color	Black
Unit Dimension (mm.)	1208*470*1688 (±5).
N/W	180Kg (±2)