

DRYER-D

บริษัท เอ็มทีเอส ซีเอ็นซี ซิสเต็ม จำกัด 48/300 ซ.หทัยราษฎร์ 37 ถ.หทัยราษฎร์ แขวง สามวาตะวันตก เขตคลองสามวา กรุงเทพฯ 10510

โทร: 02-9067988 MB: 092-2753497 Line ID : dryer-d , Line@ : @dryer-d E-mail: dryer.dservice@gmail.com www.dryer-d.com

Specification Dehumidifier Model: DDH-50



Model	DDH-50
Series	Commercial
Voltage/Cycle	220V / 50Hz
Power Input (W)	920W
Running Current	4.3A
Dehumidifying Capacity	50L/Day (30°C, 80%RH)
Humidity Set	20% - 90% RH
Humidity level can be set	+/- 1%RH
Working mode humidity set	Stop the operation when the desired humidity value is obtained.
Working mode "OP"	Continues to work until the humidity is the lowest.
Coverage area	40 - 60 sq.m (High 3 m)
Refrigerant	R410A
Air Flow	560 m ³ /h, 329 cfm
Drainage Method	8L (±0.2) / Direct Drain
Working temperature range	5°C- 38°C
Status Indicator	Bucket full, Show red light
Maneuverability	4 Casters, Handle
Control Type	Digital, Computer
Sensor	Humidity sensor "RHI"
Noise	≤60dB at a distance of 1 m.
Compressor	Rotary
Safety	3 min delay protection Bucket full alarm, Show red light Show Failure Code
Color	White & Gray
Unit Dimension (mm.)	486*332*690 (±5).
N/W	31Kg (±2)