

DRYER-D

บริษัท เอ็มทีเอส ซีเอ็นซี ซิสเต็ม จำกัด 48/300 ซ.หทัยราษฎร์ 37 ถ.หทัยราษฎร์ แขวง สามวาตะวันตก เขตคลองสามวา กรุงเทพฯ 10510

โทร: 02-9067988 MB: 092-2753497 Line ID : dryer-d , Line@ : @dryer-d E-mail: dryer.dservice@gmail.com www.dryer-d.com

Specification Industrial Ultrasonic Humidifier Model: DEW-03HS



Model	DEW-03HS
Voltage/Cycle	220V / 50Hz
Power Input (W)	200 W
Hourly Humidifying Capacity	3 kg/h
Atomizing plates	1 set / 6 Atomizing plates
Humidity Set	1% - 99%RH
Humidity level can be set	1%RH
Coverage area	40 m ² / 120 m ³ (High 3 m)
Adjustable mist level	1% - 100%
Number of fans	1 Axial Fan
Wind speed	2.5 m/s per unit / 73 m ³ /h
Mist outlet diameter (D)	75 mm
Spray hole diameter (d)	16 mm
Number of spray holes (D÷d) ²	(75÷16) ² = 22 holes
Pipe length not exceeding	Less than or equal to 7 m
Mode of Control	Wired remote control
Working water temperature	1-35°C
Working water pressure	0.1 – 0.4 Mpa
Type of water used	Tap water or clean water
Material	Stainless Steel 304
Adding water to the machine	Direct pipe connection or water pump.
Safety / Features	Overload protection, Solenoid valve, Overflow drain, Waterproof Power supply
Unit Dimension (mm.)	360*200*265(±5).
Maneuverability	Easy to move
Color	White
N/W	7.9 Kg (±2)