

DRYER-D

บริษัท เอ็มทีเอส ซีเอ็นซี ซิสเต็ม จำกัด 48/300 ซ.หทัยราษฎร์ 37 ถ.หทัยราษฎร์ แขวง สามวาตะวันตก เขตคลองสามวา กรุงเทพฯ 10510

โทร: 02-9067988 MB: 092-2753497 Line ID : dryer-d , Line@ : @dryer-d E-mail: dryer.dservice@gmail.com www.dryer-d.com

Specification Industrial Ultrasonic Humidifier Model: DEW-30HDA



Model	DEW-30HDA
Voltage/Cycle	220V / 50Hz
Power Input (W)	1800 W
Hourly Humidifying Capacity	30 kg/h
Atomizing plates	6 set / 10 Atomizing plates
Humidity Set	1% - 99%RH
Humidity level can be set	1%RH
Coverage area	300 m ² / 900 m ³ (High 3 m)
Adjustable mist level	1% - 100%
Number of fans	2 Axial Fan
Wind speed	8.2 m/s per unit / 755 m ³ /h
Mist outlet diameter (D)	160 mm x 2
Spray hole diameter (d)	32 mm
Number of spray holes (D÷d) ²	(160÷32) ² = 25 holes
Pipe length not exceeding	Less than or equal to 16 m
Mode of Control	Touch control
Working water temperature	1-35°C
Working water pressure	0.1 – 0.4 Mpa
Type of water used	Tap water or clean water
Material	Stainless Steel 304
Adding water to the machine	Direct pipe connection or water pump.
Safety / Features	Overload protection, Solenoid valve, Overflow drain, Waterproof Power supply
Unit Dimension (mm.)	800*520*525(±5).
Maneuverability	Easy to move with 4 wheels
Color	White
N/W	33 Kg (±2)