

DRYER-D

บริษัท เอ็มทีเอส ซีเอ็นซี ซิสเต็ม จำกัด 48/300 ซ.หทัยราษฎร์ 37 ถ.หทัยราษฎร์ แขวง สามวาตะวันตก เขตคลองสามวา กรุงเทพฯ 10510

โทร: 02-9067988 MB: 092-2753497 Line ID : dryer-d , Line@ : @dryer-d E-mail: dryer.dservice@gmail.com www.dryer-d.com

Specification Ultrasonic Atomizing Sterilizer Humidifier Model: DEW-40UAS



Model	DEW-40UAS
Voltage/Cycle	220V / 50Hz
Power Input (W)	3500 W
Hourly Humidifying Capacity	40 kg/h
Atomizing plates	8 set / 10 Atomizing plates
Humidity Set	1% - 99%RH
Humidity level can be set	1%RH
Coverage area	500 m ² / 1500 m ³ (High 3 m)
Adjustable mist level	Rotate to adjust fan speed
Number of fans	2 Axial Fan
Wind speed	8.2 m/s per unit / 755 m ³ /h
Mist outlet diameter (D)	110 mm
Spray hole diameter (d)	22 mm
Number of spray holes (D÷d) ²	(110÷22) ² = 25 holes
Pipe length not exceeding	Less than or equal to 16 m
Chemicals or disinfectants	Hydrogen Peroxide (H ₂ O ₂) Hypochlorous Acid (HClO) Sodium hypochlorite (NaClO) Ozone
Working water pressure	0.1 – 0.4 Mpa
Type of water used	Tap water or clean water
Material	Polyethylene (PE)
Adding water to the machine	Direct pipe connection or water
Safety / Features	Overload protection, Solenoid valve, Overflow drain, Waterproof Power supply
Unit Dimension (mm.)	720*550*700(±5).
Maneuverability	Easy to move with 4 wheels
Color	Blue and orange
N/W	36 Kg (±2)