

DRYER-D

บริษัท เอ็มทีเอส ซีเอ็นซี ซิสเต็ม จำกัด 48/300 ซ.หทัยราษฎร์ 37 ถ.หทัยราษฎร์ แขวง สามวาตะวันตก เขตคลองสามวา กรุงเทพฯ 10510

โทร: 02-9067988 MB: 092-2753497 Line ID : dryer-d , Line@ : @dryer-d E-mail: dryer.dservice@gmail.com www.dryer-d.com

Specification Ceiling Dehumidifier Model: DL-138D-D



Model	DL-138D-D
Series	Ceiling Dehumidifier
Voltage/Cycle	220V / 50Hz
Power Input (W)	1300 W
Dehumidifying Capacity	138 L/Day (30°C, 80%RH)
Dehumidifying Capacity	5.75 L/hr (30°C, 80%RH)
Humidity Set	31% - 90%RH
Humidity level can be set	+/- 1%RH
Coverage area	120 – 150 sq.m (High 3 m)
Refrigerant	R410A
Air Flow	High 1000 m ³ /h, 588 cfm Low 800 m ³ /h, 470 cfm
Air inlet and Outlet size	200 mm / 7.8"
Fresh Air inlet size	150 mm / 5.9"
Fan Speed	Centrifugal fan 2 speed (Low, High)
Static pressure	437 Pa excluding air filter
Filter	Nylon Filter
Working temperature range	5°C- 38°C
Drainage Method	Direct Drain External pipe 16 mm
Noise	≤60 dB at a distance of 1 m.
Choose to use 1 mode	1.Inner Dehum
Safety / Features	3 min delay protection, Show Failure Code, Auto Restart, Timer 1-24 Hr, Show Room Temp, Automatic Defrost,
Unit Dimension (mm.)	800*560*400 (±5).
Color	Black
N/W	65 Kg (±2)